Data Sheet: MP4P.539.R1.ENG

www.aep.it

MP4Plus

PANEL MOUNTED PROFESSIONAL INDICATOR with 4 independent channels

Measurement of: WEIGHT, FORCE, PRESSURE, DISPLACEMENT, TEMPERATURE TORQUE, ANGLE and SPEED.



"THE EVOLUTION OF THE SPECIES": after more than 30 years of service in the various versions the new MP4Plue is born.

MP4*Plus* is a Professional Digital Laboratory Indicator with **4 inputs**, suitable for receiving signals from strain gauge sensors, transmitters with voltage or current output, PT100, potentiometer and ENCODER.

Particularly suitable for both static and dynamic applications, for calibration and verification in metrology laboratories or industrial environments where it is necessary to make measurements of weight, force, pressure, torque, displacement and temperature.

To **FIT EVERY APPLICATION** the instrument can be configured and customized: the function keys F1, F2, F3 and F4 can be programmed for the function of interest such as: PEAK, HOLD, RELEASE, TX DATA DATALOG, DISCHARGE, ZOOM.

MP4*Plus* allows you to enable and disable each channel and using the **ZOOM** function it s possible to display only the channel of interest in full screen.

The instrument works with a resolution of ± 100.000 divisions and exceeds 0.005% accuracy due to an internal 24-bit Sigma-Delta AD converter and a measurement control system working at a frequency equal to the sampling frequency: this system provides a better suppression of interference caused by offset drift and connecting cables. The sampling frequency can be set from 2.5 samples per second up to 4800 samples per second therefore the

instrument is suited for applications that require a considerable speed of response.

Each input channel can be supplied in 6 different configurations:

- Version with **input for strain gauge transducers** with standard resolution of ± 100.000 div. suitable for working with load cells or force transducers with output ± 2 mV/V or ± 3 mV/V and 4 wires or 6 wires connection.
- Version with **voltage input** with standard resolution of ±100.000 div. suitable for working with pressure, torque transmitters, etc ... with output ±10V or ±5V.
- Version with **current input** with a standard resolution of ±160.000 div. suitable for working with pressure, torque transmitters, etc ... with output 4-20mA or 0-20mA with 2 or 3 wires connections.
- Version with **temperature input** for PT100 eligible to work in the range from -50 °C to + 250 °C with 0.1 °C resolution and accuracy ± 1 °C.
- Version with **incremental ENCODER input** suitable for working with linear or rotary encoders. You can also define whether to measure angle, displacement or speed.

• Version with **POTENTIOMETER input** suitable for working with linear transducers or displacement. **MP4***Plue* has as standard configuration:

- 4 DIGITAL INPUT 24Vdc with programmable functions.
- **5** programmable **SET POINTS**.
- **5 RELAYS** type DPDT. The relays can be programmed, in combination with the setpoint, to create a simple automation or logics of intervention.
- A powerful **DATALOGGER** with non-volatile memory, which allows to store data at the maximum acquisition speed, synchronizes recordings with an internal clock-calendar and can eventually export data to a USB stick in .csv file format that can be transferred directly to Microsoft Excel.
- A rear **USB** port to connect directly to a PC or Tablet.

As **OPTIONS**, the instrument can be equipped with:

- One, two, three or four Analog Outputs programmable as voltage (± 10V, 0/5V, 0/10V, ±5V) or current (4-20mA, 0-20mA, 0-24mA) that can be associated to different channels or to the TOTAL (sum of two or more channels). The refresh rate of the analog signals is equal to the frequency of acquisition of the respective channels in input.
- A serial **RS232C** line to directly connect the device to a PC, PLC or a serial **PRINTER**. Moreover, **MP4**^{2/us} can be programmed to work as **REPEATER**.
- A serial **RS485** line with protocol MODBUS RTU normally used to connect multiple instruments in a same network to a PLC.
- A front panel **USB port type A**, to export directly on a USB stick a datalogger in csv file format for a complete compatibility with Microsoft Excel

Other features and functions of importance are:

- Graphical, large and high-resolution LCD display with backlit.
- Automatic **UNIT CONVERSIONS** in many specific units for each type of transducer.
- **MULTIMETER** function which displays the signal of the sensor directly in mV/V, V or mA.
- User selectable language: ITALIAN or ENGLISH.
- Function **ZERO** and **AUTOZERO** to reset automatically the measure if the measurement is below a set threshold.
- Function of **HOLD**, **PEAK**, programmable **FILTER**.
- Function of **DISCHARGE** in order to measure the amount of product discharged for example from a tank.
- Function **TOTAL** to perform the sum of two or more channels.
- Function **KEY LOCK** to protect the instrument settings by unauthorized persons.
- 24 columns **PRINTER** (option) connected to the serial port through which it is possible to print the measuring points with the date and time and the data of the company that carried out the survey.
- REPEATER Function: The instrument can be configured to display (in the form passive as Slave) measures from the RS232C serial port (for example from another MP4244 Master) to a remote view of the measures.
 In this case all the features analysed on the MP424 Slave will be active (Setneint USP, printer, logger, etc.). The
- In this case all the features enabled on the **MP4**²⁴ Slave will be active (Setpoint, USB, printer, logger etc). The **REPEATER** function is active for one channel.

For each input channel, you can calibrate the signal coming from the sensor both in the **POSITIVE RANGE** and in the **NEGATIVE RANGE** (Example in tension and compression) through 3 different modes:

- Calibration with **Full Scale**: characterization through the programming of the transducer full scale and sensitivity in both the positive and negative range.
- Calibration for **POINTS**: linearity correction by programming 5 known points in both the positive and negative range.
- Known Weight: practice characterization (in the field) by imposing a known weight, pressure, torque to the sensor and calibrating the transducer output to this reference value.

To increase security the instrument has the ability to perform a **BACKUP** of all calibrations data so that you can recall them in case of accidental tampering.

MP4^{Plus} can be accompanied by the PC program **MP Supervisor** (Option) which allows easy connection between the instrumento and the pc over USB and allows you to display graphs or export data to Microsoft Excel. The program also allows you to download the data log either stored on the internal memory or on a USB stick and easily compare the measurements.

AEP

Typical applications:

Automatic weighing systems and small dosages. Systems for monitoring levels of tanks, silos and hoppers. Integrated measuring systems on test benches and testing. Measurement systems integrated into automated processes. Control systems of industrial processes. Automatic systems Testing and Quality Control in production lines. Control measures on board for materials testing machines. Control measures on springs, friction detection, breakout forces, leakage tests. Tests on protective and safety devices.

STANDARD CONFIGURATION



TECHNICAL DATA

STARDARD NUMBER OF CHANNELS	4 (CH1 - CH2 - CH3 - CH4)		
ACCURACY	≤± 0,010 %		
LINEARITY ERROR	≤± 0,010 %		
INTERNAL DIVISIONS	24 bit		
INPUT: STRAIN GAUGE TRANSDUCERS	$\pm 2 \text{ mV/V}$ and $\pm 3 \text{ mV/V}$ (max $\pm 3.5 \text{ mV/V}$)		
RESOLUTION	± 100.000 div		
TRANSDUCERS POWER SUPPLY	5 Vdc switching (+3 %)		
TYPE OF CONNECTION	4 or 6 wires		
TRANSDUCER RESISTANCE	from 1000 to 20000		
TRANSDUCERS CONNECTED IN PARALLEL	For each channel: 4 to 3500 or 8 to 7000		
INPUT: VOLTAGE AMPLIFIED TRANSDUCERS	+ 10V e + 5V		
RESOLUTION	+ 100 000 div		
TRANSDUCERS POWER SUPPLY	20 Vdc (+1Vdc)		
	0_20 mA		
RESOLUTION	+200 000 div +160 000 div		
	+200.000 ulv +100.000 ulv		
	±0.1 °C		
	linear and rotary encoders		
TYPE OF INPUT	RS422 line driver power supply 5Vdc (A+, A-, B+, B-)		
	5Vdc Open Collector (A, B)		
	TTL (A, B)		
	m, dm, cm, mm, μm, foot, inch		
Unit Conversions for SPEED	(degrees)		
	mm/min, m/min, ft/min, in/min, mm/s, m/s, ft/s, in/s		
	1pm, m		
	Pmin 1kO		
	R min. 1 kΩ		
INPUT: POTENTIOMETER POWER SUPPLY	R min. 1 kΩ 5 Vdc		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE	R min. 1 kΩ 5 Vdc °C, °F		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for DEESCURE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE Unit Conversions for TORQUE Unit Conversions for TORQUE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, μm		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION PACKUT CRAPHIC DISPLAY	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, μm Direct Display in mV/V, Volt or mA		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADUISTING DISPLAY CONTRAST	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, μm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated)		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CAUBRATION	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION EIELD LUNEABITATION	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKLIP AND RESTORE FUNCTION	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION EUNCTION OF ZERO	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range)		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO ELINCTION OF ZERO	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF AUTOZERO ELINCTION OF PEAK	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF PEAK FUNCTION OF DISCHARGE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for PRESSURE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF PEAK FUNCTION OF DISCHARGE ELINCTION OF KEY BLOCK	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE YES		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF AUTOZERO FUNCTION OF DISCHARGE FUNCTION OF ISCHARGE FUNCTION OF TOTAL (on all enabled channels)	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE YES Enabled through a Password		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF AUTOZERO FUNCTION OF DISCHARGE FUNCTION OF TOTAL (on all enabled channels) PROGRAMMABLE RESOLUTION	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~ 4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE YES Enabled through a Password YES		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF AUTOZERO FUNCTION OF DISCHARGE FUNCTION OF TOTAL (on all enabled channels) PROGRAMMABLE RESOLUTION	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE YES Enabled through a Password YES 1 100		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF AUTOZERO FUNCTION OF DISCHARGE FUNCTION OF DISCHARGE FUNCTION OF TOTAL (on all enabled channels) PROGRAMMABLE RESOLUTION DIGITAL FILTER	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~ 4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE YES Enabled through a Password YES 1 100 0 5		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF AUTOZERO FUNCTION OF DISCHARGE FUNCTION OF TOTAL (on all enabled channels) PROGRAMMABLE RESOLUTION DIGITAL FILTER PROGRAMMABLE CONVERSION RATE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~ 4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE YES Enabled through a Password YES 1 100 0 5 0 5		
INPUT: POTENTIOMETER POWER SUPPLY Unit Conversions for TEMPERATURE Unit Conversions for WEIGHT and FORCE Unit Conversions for TORQUE Unit Conversions for TORQUE Unit Conversions for DISPLACEMENT MULTIMETER FUNCTION BACKLIT GRAPHIC DISPLAY CHARACTER SIZE ADJUSTING DISPLAY CONTRAST TRANSDUCER CALIBRATION TYPE OF DIGITAL CALIBRATION FIELD LINEARITATION BACKUP AND RESTORE FUNCTION FUNCTION OF ZERO FUNCTION OF AUTOZERO FUNCTION OF DISCHARGE FUNCTION OF TOTAL (on all enabled channels) PROGRAMMABLE RESOLUTION DIGITAL FILTER PROGRAMMABLE CONVERSION RATE INSTRUMENT LANGUAGE	R min. 1 kΩ 5 Vdc °C, °F Kg, t, N, daN, kN, MN, lb, klb bar, mbar, psi, MPa, kPa, Pa, mH ₂ O, inH ₂ O, kg/cm ² mmHg, cmHg, inHg, atm N·m, N·mm, kN·m, kg·m, g·cm, kg·mm, ft·lbf, in·lbf mm, m, foot, inch, cm, dm, µm Direct Display in mV/V, Volt or mA 128 x 64 dots ~ 4 mm (~13 mm when ZOOM is activated) YES Both in the POSITIVE and NEGATIVE range Full Scale, Point Interpolation, Known Weight On 1 5 measurement point Save and restore all configuration data 100% (on all the measurement range) With TIME and THRESHOLD programming POSITIVE and NEGATIVE YES Enabled through a Password YES 1 100 0 5 0 5 from 2.5 to 4800 samples for second ITALIAN and ENGLISH		

DATA LOGGER allows you to store the measurements and to keep them in internal memory even if you turn off the instrument.				
The logging can be done in AUTO mode or MANUAL mode.				
The AUTO mode records the measurements at regular intervals for a programmable time. The time interval between two				
measurements points can be varied from the maximum speed of reading (4,8 kHz) up to recording every 24 hours.				
The MANUAL mode allows the operator to decide when to	o record the measurements on memory. The command can be given			
eitner via a button on the front panel or via a digital input.				
All data can be subsequently displayed on the display, down	nioaded through the powerful software MPSupervisor or exported to			
external Flash Memory (USB stick) for charting, data process	sing on Microsoft Excel, press reports etc			
INTERNAL DATA LOGGER (non volatile memory)	1 shares dissely a shift of some 120,000			
Max storing points	1 channel enabled: max. 130.000			
	2 channels enabled: max. 65.000			
	3 channels enabled: max. 32.000			
	4 channels enabled: max. 43.000			
	4 channels enabled +101AL: max. 26.000			
MAXTIME	100 days			
CLOCK CALENDAR	Year, Month, Day, Hour, Minute, Seconds			
PROGRAMMABLE SET POINT	5			
DIGITAL INPUT with programmable function	4			
RELAYS OUTPUT – contact DPDT form	5			
MAX VOLTAGE	220 Vdc – 250 Vac			
MAX CURRENT	2 A			
MAX POWER	60 W – 62,5 VA			
Rear Panel USB output, Connector type B	Max Cable Length 3.5 m			
NOMINAL WORKING TEMPERATURE	0 +50 °C			
MAX WORKING TEMPERATURE	0+50 C			
STORAGE TEMPERATURE	-20+70 C			
TEMPERATURE EFFECTS on the measurements				
a) on zero (10 °C variation)	≤10,005 %			
b) on full scale (10 °C variation)	≤±0,005 %			
POWER SUPPLY	230 Vac ±10 %			
FREQUENCY	50/60 Hz			
EXTERNAL PROTECTION FUSE	250 mA / 250 V			
MAX. POWER REQUIRED	10 VA			
PANEL MOUNTING CASE	DIN 43700			
CASE MATERIAL	NORYL UL94 V-O			
FRONT AND REAR PANEL MATERIAL	UL94 V-2			
PROTECTION CLASS (EN 60529)	IP40 (only front panel)			
DEGREE OF ENVIRONMENTAL CONT.	1			
DIMENSIONS (HxLxD) mm	72 x 144 x 150 mm			
DRILLING TEMPLATE (A x L) mm	.0 9 kg			
WEIGHT	~ 0,0 kg			

OPTIONS

RS232C SERIAL LINE	MAX cable Lenght 13 m			
RS485 MODBUS RTU (max 32 in multipoint)	MAX cable Lenght 1000 m			
PRINTER	24 columns (RS232C)			
	The USB, RS232C and RS485 are INDEPENDENT so it is possible to connect at the same time a PC, a PLC and a 24 columns serial PRINTER. On the report is it possible to print up to 3 header lines with the company data. A measurement point will be printed by pressing the key PRINT or using a remote digital command. You can print on both paper and adhesive labels.			
Analog Outputs	1 or 2 outputs independent			
Current Output	0-20 mA, 4-20 mA, 0-24 mA			
Voltage Output (max 20 mA – RL min: 1 kΩ)	0-5 V, 0-10 V, ± 10 V, ± 5 V			
Front Panel USB connector (type A) that allows you to save or export the recorded measurements directly on a USB stick, for				
faster portability of the measures on PC.				
It is possible to export the file in TXT or CSV for a direct import of the measures on programs such as Microsoft Excel.				
POWER SUPPLY	115 Vac o 24 Vdc			

COMPONENTS SUPPLIED







N° 4 connector DB9

male for transducer



CD with Manual and USB Driver

COMPONENTS IN OPTION (purchased separately)

ELECTRICAL CONNECTION





DB9 Male Connector for transducers



Desktop 24 columns printer



MP Supervisor (Option)

A dedicated program that allows an immediate interfacing through the USB port with the MP4Plus and allows you to view graphs, export data to Microsoft Excel directly from the PC and set all configuration parameters.

The program also allows you to download a Data Logger carried out using the internal memory or the USB Flash Memory and display the respective curves of acquisition.









BALANCING Ability to view both the weights of 4 distinct cells that TOTAL weight.



Dimensions (mm)



MOUNTING PANEL APPLICATION



PURCHASE CODE

	Power	Analog Output	Serial Output	Function
MP4P	XXX	XX	Х	X
	230	A1	S	F
	230 Vac	1 Output	RS232C, RS458	USB Front for
			Modbus, Printer	Flash Memory
	115	A2		
	115Vac	2 Output		
	24	A3		
	24Vdc	2 Output		
		A3		
		4 Output		

Example: MP4P230 (MP4Plus power supply 230Vac base version)
Example: MP4P24A2S (MP4Plus power supply 24Vdc + 2 analog output + Serial Output)
Example: MP4P115SF (MP4Plus power supply 115Vac + Serial Output + USB Flash Memory)



<u>ALWAYS SPECIFY</u> in the purchase order how to configure the input channels. After the sale, the inputs <u>can not be changed</u> by the customer.

Example of channel configuration CH1: 2mV/V, 4-20mA, $\pm 10V$, POTENTIOMETER Example of channel configuration CH2: 2mV/V, 4-20mA, $\pm 10V$, POTENTIOMETER, PT100, ENCODER Example of channel configuration CH3: 2mV/V, 4-20mA, $\pm 10V$, POTENTIOMETER Example of channel configuration CH4: 2mV/V, 4-20mA, $\pm 10V$, POTENTIOMETER, PT100, ENCODER

